

Standard Accessories

	<p>SP-5100</p>
	
	<p>FLEXIBLE CLAMP FOR AC CURRENT Measuring range: 5A÷3000A Basic accuracy: ±0.5%reading Measurement category: CAT III 600V Clamp jaw internal diameter: 174mm Output connector: Hypertac</p>
	<p>Soft bag with two big compartments to transport devices and accessories.</p>
	<p>PR400 REMOTE LEAD WITH TEST STARTING BUTTON Measurement category: CAT IV 600V / CAT III 1000V Overall length: 25cm Tip length: 1.9cm Tip diameter: 4mm</p>
	<p>C2033X CABLE WITH BANANA GREEN - BLACK - BLUE SHUKO PLUG Measuring range: 16A / 300V Measurement category: CAT III 300V Overall length: 1.5m Banana diameter: 4mm</p>
	<p>UNIVERSALKITG3 SET OF 4 CABLES, 4 ALLIGATOR CLIPS AND 3 LEADS BLACK RED-GREEN-BLUE Measuring range: 10A / 1000V Measurement category: CAT IV 600V / CAT III 1000V Cable length: 2m Maximum opening of alligator clip: 4cm Banana diameter: 4mm</p>
	<p>RECHARGEABLE BAT Battery type: AA Composition: Ni-MH Rated voltage: 1.2V Power: min 2000mAh</p>

	<p>SUPPLY CABLE FOR HT7051 verall length: 2m Connectors: Europlug with no earthing Shuko CEE 7/17</p>
	<p>SET OF 4 RODS AND 4 CABLE COILS BLUE-RED-GREEN-BLACK Length of rods: 25cm Blue cable length: 25m Red cable length: 20m Green-black cable length: 4.5m Measurement category: CAT III 600V Banana diameter: 4mm</p>
	<p>TOPVIEW2006 MULTI-LANGUAGE SOFTWARE TOPVIEWS FOR MANAGEMENT OF Cable length: 1.5m Output connector: USB Compatibility: Windows XP-7-8-10</p>

Optional accessories

	<p>HT97U STANDARD CLAMPS FOR AC CURRENT Measuring range: 0.1÷1000A Basic accuracy: ± 1.0%reading Measurement category: CAT III 600V Clamp jaw internal diameter: 54mm Output connector: Hypertac</p>
	<p>HP30C2 STANDARD CLAMPS FOR AC CURRENT Ranges: 200 / 2000A Measuring range: 0.1A÷2000A Basic accuracy: ±0.5%reading Measurement category: CAT III 600V Clamp jaw internal diameter: 70mm Output connector: Hypertac</p>
	<p>HP30C3STANDARD CLAMPS FOR AC CURRENT Ranges: 200 / 3000A Measuring range: 1A÷3000A Basic accuracy: ±0.5%reading Measurement category: CAT III 600V Clamp jaw internal diameter: 70mm Output connector: Hypertac</p>
	<p>HT4005K STANDARD CLAMP FOR AC CURRENT Measuring range: 0.1÷200A Basic accuracy: ±0.5%reading Measurement category: CAT III 600V Clamp jaw internal diameter: 40mm Output connector: Hypertac</p>
	<p>HT4005N STANDARD CLAMP FOR AC CURRENT Campo di misura: 0.005A÷100A Diametro Interno toroide: 20mm Precisione base: ±1% della lettura Connettore in uscita: Hypertac</p>
	<p>HTFLEX35 FLEXIBLE CLAMP FOR AC CURRENT Measuring range: 5A÷3000A* Basic accuracy: ±0.5%reading Measurement category: CAT III 600V Clamp jaw internal diameter: 274mm Output connector: Hypertac *With PQA819/PQA820 max 1000A</p>

	<p>HT98U STANDARD CLAMP FOR DC CURRENT Measuring range: 1÷1000A Precision base: $\pm(1.0\% \text{reading} + 0.5A)$ Basic accuracy: CAT III 600V Clamp jaw internal diameter: 52mm Output connector: Hypertac</p>
	<p>HP30D1 STANDARD CLAMP FOR DC CURRENT Measuring range: 10÷1000A Basic accuracy: $\pm(1.5\% \text{reading} + 2mV)$ Measurement category: CAT III 600V Clamp jaw internal diameter: 83mm Output connector: Hypertac</p>
	<p>HT4004N STANDARD CLAMP FOR DC CURRENT Ranges: 10A / 100A Basic accuracy: $\pm 1.0\% \text{reading}$ Measurement category: CAT III 300V Clamp jaw internal diameter: 32mm Output connector: Hypertac</p>
	<p>HT4004 STANDARD CLAMP FOR AC/DC CURRENT Ranges: 10A / 100A Basic accuracy: $\pm 1.0\% \text{reading}$ Measurement category: CAT III 600V Clamp jaw internal diameter: 32mm Output connector: Hypertac</p>
	<p>HT52/05 PROBE FOR AIR TEMPERATURE / HUMIDITY TEMPERATURE Range: $-20 \div 60^{\circ}C$, $4 \div 140^{\circ}F$ Accuracy: $\pm 0.7^{\circ}C$, $\pm 1.4^{\circ}F$ Type of sensor: capacitive</p> <p>HUMIDITY Range: 0÷100%RH Accuracy: $\pm 3\% \text{reading a } 25^{\circ}C$ Type of sensor: capacitive</p>
	<p>HT53/05 LIGHT METER PROBE CLASS 1 Sensor type: silicon photodiode Ranges: 20 / 2000 / 20000lux Response time: <100ms Output signal: 20 lux: 0.01lux 1mV 2000lux: 1lux 1mV 20000lux: 10lux 1mV Accuracy: $\pm 3\% \text{reading}$</p>
	<p>VA500 VA500 is the ideal solution for those who want to protect their devices from water, dust and hostile environments. It is also suitable to contain all accessories for a perfect management of the job.</p>
	<p>606-IECN CONNECTOR WITH MAGNETIC TERMINAL Measuring range: 4A / 1000V Measurement category: CAT IV 600V / CAT III 1000V Magnetic tip length: 3.5cm Banana diameter: 4mm</p>
	<p>1066-IECN CONNECTOR FOR EXTENSION BANANA IN/OUT 4MM Measuring range: 36A / 1000V Measurement category: CAT III 600V / CAT II 1000V Overall length: 5.6cm Diameter of input/output banana: 4mm</p>
	<p>T2100 CLAMP FOR MEASURING EARTH RESISTANCE WITHOUT RODS Resistance measuring range: $0.010 \div 1000\Omega$ Resolution: $0.001 \div 20\Omega$</p>

	<p>Basic accuracy: $\pm 0.01\% \text{reading} + 0.01\Omega$ Measurement category: CAT III 150V Clamp jaw internal diameter: 32mm Output connector: Jack 3.5mm Size: 293 x 90 x 66mm Weight, battery included: 1320gr</p>
	<p>1066-IECR CONNECTOR FOR EXTENSION BANANA IN/OUT 4MM Measuring range: 36A / 1000V Measurement category: CAT III 600V / CAT II 1000V Overall length: 5.6cm Diameter of input/output banana: 4mm</p>
	<p>HT4003 STANDARD CLAMP FOR AC CURRENT Measuring range: 1A ÷ 400A Basic accuracy: $\pm 1.5\% \text{reading} + 0.5A$ Measurement category: CAT III 600V Clamp jaw internal diameter: 30mm Output connector: 2x banana connector</p>
	<p>IMP57 CCESSORY FOR LOOP IMPEDANCE MEASUREMENT WITH HIGH RESOLUTION AND PROSPECTIVE SHORT-CIRCUIT CUTRRENT UP TO 400KA Type of measurement: Loop impedance P-N, P-P, P-PE and calculation of short-circuit current Measurement resolution: 0.1mΩ (Zloop); 400kA (Ipsc) Test current: approx. 200A Frequency range: 50Hz \pm 5% Size (LxWxH): 340x300x150mm</p>
	<p>RCDX10</p>