



1. ELECTRICAL SPECIFICATIONS

Accuracy is given as \pm (% of reading + no. of least significant digits) at $23^{\circ}\text{C} \pm 5^{\circ}\text{C}$, with relative humidity Less than 80% R.H.

DC VOLTAGE

Range	Resolution	Accuracy	Overload Protection
2V	1mV	$\pm(0.8\%rdg+2gt)$	600V DC/AC RMS
20V	10 mV		
200V	100 mV		
600V	1V	$\pm(1.0\%rdg+2gt)$	

Input Impedance: $10\text{M}\Omega$

AC VOLTAGE

Range	Resolution	Accuracy 50~60Hz	Overload Protection
2V	1mV	$\pm(1.0\%rdg+3dgt)$	600V DC/AC RMS
20V	10 mV		
200V	100 mV		
600V	1V	$\pm(1.2\%rdg+3dgt)$	

Input Impedance: $10\text{M}\Omega$

AC CURRENT

Range	Resolution	Accuracy 50 ~ 60Hz	Overload Protection
200A	0.1A	$\pm(2.0\%rdg+10dgt)$	600A RMS (60 second)
400A	1A		

RESISTANCE

Range	Resolution	Accuracy	MAX. Test Voltage	Overload Protection
200 Ω	0.1 Ω	$\pm(1.0\%rdg+5dgt)$	About 1.5 VDC	600V RMS (60 second)
2k Ω	1 Ω	$\pm(1.0\%rdg+3dgt)$	About 0.45 VDC	
20k Ω	10 Ω			
200k Ω	100 Ω			
2M Ω	1k Ω	$\pm(3.0\%rdg+3dgt)$		
20M Ω	10k Ω			

DIODE CHECK

Range	Resolution	Accuracy	Test Voltage
Diode	10mV	$\pm(0.5\%rdg+3dgt)$	<3VDC

Overload protection: 500V RMS

AUDIBLE CONTINUITY TEST

Range	Accuracy	Test Voltage
Continuity	Built-in buzzer sounds when reading is below approx. 25 Ω , the buzzer turns off when reading is greater than 25 Ω .	<1.5VDC

Overload protection: 500V RMS



2. GENERAL SPECIFICATIONS

Display:

- The liquid crystal display (LCD) is 3 ½ digits with maximum reading 1900 counts.
- Decimal point and symbol indication
- Automatic polarity indication.

Function:

- DCV, ACV, ACA, OHM, Diode check and Audible continuity tests.

Measuring rate:

- 2 times per second.

Low battery indicator:

- The "  " appears when the battery voltage drops is low

Operating temperature:

- 5°C to 40 °C, 0 - 80 % R.H.

Storage temperature:

- -10°C to 60°C, 0 - 70 % R.H.

General informations:

- Indoor use
- Altitude up to 2000m
- Pollution degree: 2
- Insulation: class 2 (double insulation)
- Max. diameter conductor : 30 mm

Power supply:

- 2 x 1.5V IEC R03 AAA carbon-zinc or alkaline type batteries
- AutoPowerOFF function for more of 10 minutes of don't work

Dimension:

- 205 (H) x 64 (W) x 39 (L) mm

Weight:

- 280 grams with batteries included.

Applied standards:

- LVD: EN 61010-1 CAT III 600V
- EMC: EN60326

This product conforms to the prescriptions of the European directive on low voltage 2006/95/EEC and to EMC directive 2004/108/EEC